

DAFTAR PUSTAKA

- Ates, M., & Yuruk, Y. (2021). Facile preparation of reduced graphene oxide, polypyrrole, carbon black, and polyvinyl alcohol nanocomposite by electrospinning: a low-cost and sustainable approach for supercapacitor application. *Ionics*, 27(6), 2659–2672. <https://doi.org/10.1007/s11581-021-04007-y>
- Bellettini, I. C., Nandi, L. G., Eising, R., Domingos, J. B., Machado, V. G., & Minatti, E. (2012). Properties of aqueous solutions of hydrophobically modified polyethylene imines in the absence and presence of sodium dodecylsulfate. *Journal of Colloid and Interface Science*, 370(1), 94–101. <https://doi.org/10.1016/j.jcis.2011.12.049>
- Bhajantri, R. F., Ravindrachary, V., Harisha, A., Crasta, V., Nayak, S. P., & Poojary, B. (2006). Microstructural studies on BaCl₂ doped poly(vinyl alcohol). *Polymer*, 47(10), 3591–3598. <https://doi.org/10.1016/j.polymer.2006.03.054>
- Bhardwaj, U., Sura, R., Papadimitrakopoulos, F., & Burgess, D. J. (2010). PLGA/PVA hydrogel composites for long-term inflammation control following s.c. implantation. *International Journal of Pharmaceutics*, 384(1–2), 78–86. <https://doi.org/10.1016/j.ijpharm.2009.09.046>
- Bimantara, T., Juningtyastuti, & Facta, M. (2016). Kinerja rangkaian r-c dan r-l-c dalam pembangkitan tegangan tinggi impuls. 2016, 2–8.
- Cahyono, B. E., Misto, M., & Hasanah, F. (2016). Karakterisasi Sensor Kapasitif Untuk Penentuan Level Aquades. *Rekayasa Energi Manufaktur*, 1(2), 9. <https://doi.org/10.21070/r.e.m.v1i2.583>
- Chiappetta, D. A., & Sosnik, A. (2007). Poly(ethylene oxide)-poly(propylene oxide) block copolymer micelles as drug delivery agents: Improved hydrosolubility, stability and bioavailability of drugs. *European Journal of Pharmaceutics and Biopharmaceutics*, 66(3), 303–317. <https://doi.org/10.1016/j.ejpb.2007.03.022>
- De Geyter, N., Morent, R., Leys, C., Gengembre, L., & Payen, E. (2007). Treatment of polymer films with a dielectric barrier discharge in air, helium and argon at medium pressure. *Surface and Coatings Technology*, 201(16–17), 7066–7075. <https://doi.org/10.1016/j.surfcoat.2007.01.008>
- Deng, X., Zhang, L., Guo, J., Chen, Q., & Ma, J. (2017). ZnO enhanced NiO-based gas sensors towards ethanol. *Materials Research Bulletin*, 90, 170–174. <https://doi.org/10.1016/j.materresbull.2017.02.040>

- Dielektrik, K., Kertas, B., & Pada, K. (2014). Konstanta Dielektrik Bahan Kertas Karton Pada Keping Sejajar. *Jurnal Fisika*, 4(2), 1–1. <https://doi.org/10.15294/jf.v4i2.3829>
- Ding, B., Kim, J., Miyazaki, Y., & Shiratori, S. (2004). Electrospun nanofibrous membranes coated quartz crystal microbalance as gas sensor for NH₃ detection. *Sensors and Actuators, B: Chemical*, 101(3), 373–380. <https://doi.org/10.1016/j.snb.2004.04.008>
- El Fawal, G. F., Hassan, H. S., El-Aassar, M. R., & Elkady, M. F. (2019). Electrospun Polyvinyl Alcohol Nanofibers Containing Titanium Dioxide for Gas Sensor Applications. *Arabian Journal for Science and Engineering*, 44(1), 251–257. <https://doi.org/10.1007/s13369-018-3529-z>
- Fisika, K., & Ii, D. (2009). *Rangkaian RC*. 1–12.
- Fratoddi, I., Venditti, I., Cametti, C., & Russo, M. V. (2015). Chemiresistive polyaniline-based gas sensors: A mini review. *Sensors and Actuators, B: Chemical*, 220, 534–548. <https://doi.org/10.1016/j.snb.2015.05.107>
- Galih, V., Putra, V., Si, S., & Sc, M. (n.d.). *Perkembangan revolusi tekstil elektronik dan manufaktur*.
- García Reyes, L. E., & From 百度文库. (2013). 濟無No Title No Title. *Journal of Chemical Information and Modeling*, 53(9), 1689–1699.
- Geiselbrechtinger, A., Büyüktas, K., Allers, K.-H., & Hartung, W. (2009). A high-performance trench capacitor integrated in a passive integration technology. *Semiconductor Science and Technology*, 24(1), 015010. <https://doi.org/10.1088/0268-1242/24/1/015010>
- Harper, J. C., Christensen, P. A., Egerton, T. A., Curtis, T. P., & Gunlazuardi, J. (2001). Effect of catalyst type on the kinetics of the photoelectrochemical disinfection of water inoculated with E. coli. *Journal of Applied Electrochemistry*, 31(6), 623–628. <https://doi.org/10.1023/A:1017539328022>
- Hassan, H. S., Elkady, M. F., Farghali, A. A., Salem, A. M., & AbdEl-Hamid, A. I. (2017). Fabrication of novel magnetic zinc oxide cellulose acetate hybrid nanofiber to be utilized for phenol decontamination. *Journal of the Taiwan Institute of Chemical Engineers*, 78, 307–316. <https://doi.org/10.1016/j.jtice.2017.06.021>
- Izwan, S., Razak, A., Wahab, I. F., Fadil, F., Dahli, F. N., Khudzari, A. Z., & Adeli, H. (2015). A Review of Electrospun Conductive Polyaniline Based Nanofiber

Composites and Blends: Processing Features, Applications, and Future Directions. *Advances in Materials Science and Engineering*, 2015, 1–19.

- Kudlek, E., Silvestri, D., Waclawek, S., Padil, V. V. T., Stuchlík, M., Voleský, L., Kejzlar, P., & ČERNÍK, M. (2017). TiO₂ immobilised on biopolymer nanofibers for the removal of bisphenol A and diclofenac from water. *Ecological Chemistry and Engineering S*, 24(3), 417–429. <https://doi.org/10.1515/eces-2017-0028>
- Medvecká, V., Kováčik, D., Zahoranová, A., & Černák, M. (2017). Atmospheric pressure plasma assisted calcination by the preparation of TiO₂ fibers in submicron scale. *Applied Surface Science*. <https://doi.org/10.1016/j.apsusc.2017.09.178>
- Mironenko, A. Y., Sergeev, A. A., Nazirov, A. E., Modin, E. B., Voznesenskiy, S. S., & Bratskaya, S. Y. (2016). H₂S optical waveguide gas sensors based on chitosan/Au and chitosan/Ag nanocomposites. *Sensors and Actuators, B: Chemical*, 225, 348–353. <https://doi.org/10.1016/j.snb.2015.11.073>
- Montallana, A. D. S., Lai, B. Z., Chu, J. P., & Vasquez, M. R. (2020). Enhancement of photodegradation efficiency of PVA/TiO₂ nanofiber composites via plasma treatment. *Materials Today Communications*, 24, 101183. <https://doi.org/10.1016/j.mtcomm.2020.101183>
- Nasikhudin, Ismaya, E. P., Diantoro, M., Kusumaatmaja, A., & Triyana, K. (2017). Preparation of PVA/TiO₂ Composites Nanofibers by using Electrospinning Method for Photocatalytic Degradation. *IOP Conference Series: Materials Science and Engineering*, 202(1). <https://doi.org/10.1088/1757-899X/202/1/012011>
- Nguyen, D. N., & Yoon, H. (2016). Recent advances in nanostructured conducting polymers: From synthesis to practical applications. *Polymers*, 8(4). <https://doi.org/10.3390/polym8040118>
- Nimkar, S. H., Agrawal, S. P., & Kondawar, S. B. (2015). Fabrication of Electrospun Nanofibers of Titanium Dioxide Intercalated Polyaniline Nanocomposites for CO₂ Gas Sensor. *Procedia Materials Science*, 10(Cnt 2014), 572–579. <https://doi.org/10.1016/j.mspro.2015.06.008>
- Nur, M. (2011). *Plasma Physics and Applications*.
- Pan, J., Ganesan, R., Shen, H., & Mathur, S. (2010). Plasma-modified SnO₂ nanowires for enhanced gas sensing. *Journal of Physical Chemistry C*, 114(18), 8245–8250. <https://doi.org/10.1021/jp101072f>

- Park, J. S. (2010). Electrospinning and its applications. *Advances in Natural Sciences: Nanoscience and Nanotechnology*, 1(4). <https://doi.org/10.1088/2043-6262/1/4/043002>
- Peppas, N. A., & Hassan, C. M. (2000). Structure and applications of poly (vinyl alcohol) hydrogels produced by conventional crosslinking or by freezing / thawing methods. *Advances in Polymer Science*, 153, 37–65.
- Pratama, ferina nadya. (2020). Digital Digital Repository Repository Universitas Universitas Jember Jember Staphylococcus aureus Digital Digital Repository Repository Universitas Universitas Jember Jember. *Skripsi*.
- Putra Valentinus Galih Vidia dan Purnomosari Endah. (2015). *Pengantar Eksperimen Fisika*.
- Putra, V. G. V., Zulfikar, L., Sumihartanti, A., Mohamad, J. N., & Yusuf, Y. (2020). Tip-Cylinder Electrode Plasma to Enhance the Coating of Conductive Yarn Process. *Jurnal Rekayasa Proses*, 14(2), 213. <https://doi.org/10.22146/jrekpros.54946>
- Repository, D., Universitas, R., & Jember, U. (2021). Digital Repository Repository Universitas Universitas Jember Jember Digital Digital Repository Repository Universitas Universitas Jember Jember. In *Digital Repository Universitas Jember* (Issue September 2019).
- Servais, T., Brocke, R., & Fatka, O. (1996). Variability in the Ordovician acritarch Dicrodiacrodium. *Palaeontology*, 39(2), 389–405.
- Shahidi, S., Ghoranneviss, M., & Moazzenchi, B. (2014). New advances in plasma technology for textile. *Journal of Fusion Energy*, 33(2), 97–102. <https://doi.org/10.1007/s10894-013-9657-2>
- Sharma, S., & Madou, M. (2012). Review article: A new approach to gas sensing with nanotechnology. *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 370(1967), 2448–2473. <https://doi.org/10.1098/rsta.2011.0506>
- Sheha, E., & El-Mansy, M. K. (2008). A high voltage magnesium battery based on H2SO4-doped (PVA)0.7(NaBr)0.3 solid polymer electrolyte. *Journal of Power Sources*, 185(2), 1509–1513. <https://doi.org/10.1016/j.jpowsour.2008.09.046>
- Shi, H., Magaye, R., Castranova, V., & Zhao, J. (2013). Titanium dioxide nanoparticles: A review of current toxicological data. *Particle and Fibre Toxicology*, 10(1). <https://doi.org/10.1186/1743-8977-10-15>

- Shi, X., Zhou, W., Ma, D., Ma, Q., & Bridges, D. (2015). *Review Article Electrospinning of Nanofibers and Their Applications for Electrospinning of Nanofibers and Their Applications for*. 2015(May). <https://doi.org/10.1155/2015/140716>
- Shokry Hassan, H., Kashyout, A. B., Morsi, I., Nasser, A. A. A., & Raafat, A. (2014). Fabrication and characterization of gas sensor micro-arrays. *Sensing and Bio-Sensing Research*, 1(July), 34–40. <https://doi.org/10.1016/j.sbsr.2014.04.001>
- Shokry Hassan, H., Kashyout, A. B., Morsi, I., Nasser, A. A. A., & Abuklill, H. (2015). Development of polypyrrole coated copper nanowires for gas sensor application. *Sensing and Bio-Sensing Research*, 5, 50–54. <https://doi.org/10.1016/j.sbsr.2015.07.004>
- Stagi, L., Carbonaro, C. M., Corpino, R., Chiriu, D., & Ricci, P. C. (2015). Light induced TiO₂ phase transformation: Correlation with luminescent surface defects. *Physica Status Solidi (B) Basic Research*, 252(1), 124–129. <https://doi.org/10.1002/pssb.201400080>
- Subbiah, T., Bhat, G. S., Tock, R. W., Parameswaran, S., & Ramkumar, S. S. (2005). Electrospinning of nanofibers. *Journal of Applied Polymer Science*, 96(2), 557–569. <https://doi.org/10.1002/app.21481>
- Tai, H., Jiang, Y., Xie, G., Yu, J., & Chen, X. (2007). Fabrication and gas sensitivity of polyaniline-titanium dioxide nanocomposite thin film. *Sensors and Actuators, B: Chemical*, 125(2), 644–650. <https://doi.org/10.1016/j.snb.2007.03.013>
- Tayibnapis, A. S., & Sitohang, K. (2015). Rancang Bangun Prototip Mesin Plasma Tekstil Lucutan Korona Pada Tekanan Atmosfir Skala Laboratorium. *Arena Tekstil*, 30(1), 25–36. <https://doi.org/10.31266/at.v30i1.1946>
- Tian, W. C., Ho, Y. H., Chen, C. H., & Kuo, C. Y. (2013). Sensing performance of precisely ordered TiO₂ nanowire gas sensors fabricated by electron-beam lithography. *Sensors (Switzerland)*, 13(1), 865–874. <https://doi.org/10.3390/s130100865>
- Van Der Goes, F. M. L., & Meijer, G. C. M. (1996). A novel low-cost capacitive-sensor interface. *IEEE Transactions on Instrumentation and Measurement*, 45(2), 536–540. <https://doi.org/10.1109/19.492782>
- Wang, G., Ji, Y., Huang, X., Yang, X., Gouma, P. I., & Dudley, M. (2006). Fabrication and characterization of polycrystalline WO₃ nanofibers and their application for ammonia sensing. *Journal of Physical Chemistry B*, 110(47), 23777–23782. <https://doi.org/10.1021/jp0635819>

- Yang, A., Tao, X., Wang, R., Lee, S., & Surya, C. (2007). Room temperature gas sensing properties of Sn O₂ /multiwall-carbon-nanotube composite nanofibers. *Applied Physics Letters*, 91(13), 91–94. <https://doi.org/10.1063/1.2783479>
- Yang, X., Liu, Q., Chen, X., Yu, F., & Zhu, Z. (2008). Investigation of PVA/ws-chitosan hydrogels prepared by combined γ -irradiation and freeze-thawing. *Carbohydrate Polymers*, 73(3), 401–408. <https://doi.org/10.1016/j.carbpol.2007.12.008>
- Yuniar, R. A., Widiyastuti, W., Setyawan, H., Purwaningsih, H., Machmudah, S., & Anggoro, D. (2019). Formation of Carbon Fibres from Polymer Poly(vinyl alcohol)/Acetylene Black using Electrospinning Method. *IOP Conference Series: Materials Science and Engineering*, 543(1). <https://doi.org/10.1088/1757-899X/543/1/012030>
- ZHANG, L. sheng, WU, W. zhong, & WANG, J. long. (2007). Immobilization of activated sludge using improved polyvinyl alcohol (PVA) gel. *Journal of Environmental Sciences*, 19(11), 1293–1297. [https://doi.org/10.1016/S1001-0742\(07\)60211-3](https://doi.org/10.1016/S1001-0742(07)60211-3)
- Zhao, W., Fam, D. W. H., Yin, Z., Sun, T., Tan, H. T., Liu, W., Tok, A. I. Y., Boey, Y. C. F., Zhang, H., Hng, H. H., & Yan, Q. (2012). A carbon monoxide gas sensor using oxygen plasma modified carbon nanotubes. *Nanotechnology*, 23(42). <https://doi.org/10.1088/0957-4484/23/42/425502>