

**DAFTAR PUSTAKA**

Aizenshtein, E. M. (2020) 'BOTTLE WASTES – TO TEXTILE YARNS', 47(5), pp. 3–7. doi: 10.1007/s10692-016-9691-8.

Al-munif, M. *et al.* (2014) 'United States Patent 5.905.136'.

Allison, L., Hoxie, S. and Andrew, T. L. (2017) 'Towards seamlessly-integrated textile electronics: Methods to coat fabrics and fibers with conducting polymers for electronic applications', *Chemical Communications*. Royal Society of Chemistry, 53(53), pp. 7182–7193. doi: 10.1039/c7cc02592k.

Chen, J. *et al.* (2017) 'Balance the electrical properties and mechanical properties of carbon black filled immiscible polymer blends with a double percolation structure', *Composites Science and Technology*. Elsevier Ltd, 140, pp. 99–105. doi: 10.1016/j.compscitech.2016.12.029.

Chowdhury, S., Maniar, A. T. and Suganya, O. (2013) 'Polyethylene Terephthalate ( PET ) Waste as Building Solution', *International Journal of Chemical, Environmental & Biological Sciences (IJCEBS)*, 1(2), pp. 2320–4087.

Das, A. *et al.* (2009) 'Effect of various parameters on electromagnetic shielding effectiveness of textile fabrics', *Indian Journal of Fibre and Textile Research*, 34(2), pp. 144–148.

Foroughi, J. *et al.* (2010) 'The mechanical and the electrical properties of conducting polypyrrole fibers', *Journal of Applied Physics*, 107(10), pp. 1–4. doi: 10.1063/1.3425793.

Gachter, R. and Miiller, H. (1990) *Plastics additives (third edition)*. Munich: Hanser Verlag.

Gong, L. X. *et al.* (2015) 'Balanced electrical, thermal and mechanical properties of epoxy composites filled with chemically reduced graphene oxide and rubber nanoparticles', *Composites Science and Technology*, 121, pp. 104–114. doi: 10.1016/j.compscitech.2015.10.023.

Gong, T. *et al.* (2016) 'Low percolation threshold and balanced electrical and

mechanical performances in polypropylene/carbon black composites with a continuous segregated structure', *Composites Part B: Engineering*, 99, pp. 348–357. doi: 10.1016/j.compositesb.2016.06.031.

Gubbels, F. *et al.* (1998) 'Kinetic and Thermodynamic Control of the Selective Localization of Carbon Black at the Interface of Immiscible Polymer Blends', *Chemistry of Materials*. American Chemical Society, 10(5), pp. 1227–1235. doi: 10.1021/cm970594d.

Huang, J. C. (2002a) 'Carbon black filled conducting polymers and polymer blends', *Advances in Polymer Technology*, 21(4), pp. 299–313. doi: 10.1002/adv.10025.

Huang, J. C. (2002b) 'Carbon black filled conducting polymers and polymer blends', *Advances in Polymer Technology*, pp. 299–313. doi: 10.1002/adv.10025.

Huang, J. and Jiang, W. (2014) 'Control of carbon nanotubes at the interface of a co-continuous immiscible polymer blend to fabricate conductive composites with ultralow percolation thresholds Design of advanced functional epoxy composites View project-View project'. doi: 10.1016/j.carbon.2014.02.063.

Huang, Y. *et al.* (no date) 'From industrially weavable and knittable highly conductive yarns to large wearable energy storage textiles', *ACS Publications*. Available at: <https://pubs.acs.org/doi/abs/10.1021/acsnano.5b00860> (Accessed: 29 October 2018).

Jambeck, J. R. *et al.* (2015) 'Plastic waste inputs from land into the ocean', *Science*, 347(6223), pp. 764–768. doi: 10.1126/science.1260879.

Jatmiko Wahyudi, Hermain Teguh Prayitno, A. D. A. (2018) 'Pemanfaatan Limbah Plastik Sebagai Bahan Baku Pembuatan Bahan Bakar Alternatif', *Jurnal Litbang*, XIV(1), pp. 58–67.

Karuniastuti, N. (2013) 'Bahaya Plastik terhadap Kesehatan dan Lingkungan', *Swara Patra: Majalah Pusdiklat Migas*, 3(1), pp. 6–14. Available at: <http://ejurnal.ppsdmmigas.esdm.go.id/sp/index.php/swarapatra/article/view/43/65>.

Kim, B. *et al.* (2004) 'Electrical and morphological properties of PP and PET

- conductive polymer fibers', *Synthetic Metals*, 146(2), pp. 167–174. doi: 10.1016/j.synthmet.2004.06.023.
- Kuhn, H. H. *et al.* (1993) 'Properties and applications of conductive textiles', *Synthetic Metals*, 57(1), pp. 3707–3712. doi: 10.1016/0379-6779(93)90501-M.
- Lan, Y. *et al.* (2016) 'Electrically conductive thermoplastic polyurethane/polypropylene nanocomposites with selectively distributed graphene'. doi: 10.1016/j.polymer.2016.05.017.
- Liu, H. *et al.* (2017) 'Lightweight conductive graphene/thermoplastic polyurethane foams with ultrahigh compressibility for piezoresistive sensing', *Journal of Materials Chemistry C*, 5(1), pp. 73–83. doi: 10.1039/c6tc03713e.
- Liu, K. *et al.* (no date) 'Carbon nanotube yarns with high tensile strength made by a twisting and shrinking method', *iopscience.iop.org*. Available at: <http://iopscience.iop.org/article/10.1088/0957-4484/21/4/045708/meta> (Accessed: 3 December 2018).
- Lu, G., Li, X. and Jiang, H. (1996) 'Electrical and shielding properties of ABS resin filled with nickel-coated carbon fibers', *Composites Science and Technology*, 56(2), pp. 193–200. doi: 10.1016/0266-3538(95)00143-3.
- Mao, C. *et al.* (2013) 'Tailored Parallel Graphene Stripes in Plastic Film with Conductive Anisotropy by Shear-Induced Self-Assembly', *The Journal of Physical Chemistry Letters*, 4(1), pp. 43–47. doi: 10.1021/jz301811b.
- Mao, C., Zhu, Y. and Jiang, W. (2012) 'Design of electrical conductive composites: Tuning the morphology to improve the electrical properties of graphene filled immiscible polymer blends', *ACS Applied Materials and Interfaces*, 4(10), pp. 5281–5286. doi: 10.1021/am301230q.
- Mazzoldi, A. *et al.* (2002) *SMART TEXTILES FOR WEARABLE MOTION CAPTURE SYSTEMS*, *AUTEX Research Journal*. Available at: <http://www.autexrj.org/No6/0038.pdf> (Accessed: 24 January 2020).
- Meoli, D. and May-Plumlee, T. (2002) 'Interactive electronic textile development: A review of technologies', *Journal of Textile and Apparel, Technology and*

*Management*, 2(2), pp. 1–12.

Nichols, C. S. and Charlotte, N. C. (1991) ‘United States Patent ( US5008230A )’. United States.

Pandey, D. N., Basu, A. and Kumar, P. (2018) ‘Study of Electro Conductive Textiles : A Review’, *International Journal of Scientific Research Engineering & Technology*, 7(10), pp. 744–749.

Pertiwi, P. K. *et al.* (2015) ‘Uji Konduktivitas Listrik pada CaCO<sub>3</sub> dan Arang Kayu dengan Metode Four Point Probe’, pp. 3–7.

Pomfret, S. J. *et al.* (1999) ‘Advances in processing routes for conductive polyaniline fibres’, *Synthetic Metals*, 101(1), pp. 724–725. doi: 10.1016/S0379-6779(98)01220-X.

Putra, H. P. and Yuriandala, Y. (2010) ‘Studi Pemanfaatan Sampah Plastik Menjadi Produk dan Jasa Kreatif’, *Jurnal Sains & Teknologi Lingkungan*, 2(1), pp. 21–31. doi: 10.20885/jstl.vol2.iss1.art3.

Robertson, R. . (1966) ‘Polymer Order and Polimer Density’, *The Journal of Physical Chemistry*, 69(6), pp. 1575–1578.

De Rossi, D. *et al.* (2005) ‘Electroactive fabrics and wearable man-machine interfaces’, *Wearable Electronics and Photonics*, pp. 59–80. doi: 10.1533/9781845690441.59.

Sahwan, F. L. *et al.* (2005) ‘Sistem Pengelolaan Limbah Plastik di Indonesia’, *Jurnal Sistem Pengolahan Limbah J. Tek. Ling. P3TL-BPPT*, 6(1), pp. 311–318.

Scherzer, S. *et al.* (2015) ‘Phase structure, rheology and electrical conductivity of co-continuous polystyrene/polymethylmethacrylate blends filled with carbon black’, *Elsevier*. Available at:

<https://www.sciencedirect.com/science/article/pii/S0266353815301007>

(Accessed: 24 January 2020).

Schindler, W. D. and Hauser, P. J. (2004) ‘Antistatic finishes’, *Chemical Finishing of Textiles*, pp. 121–128. doi: 10.1533/9781845690373.121.

Seymour, R. and Carraher, C. (1984) *Structure-Property Relationship In Polymer*.

Shukla, S. R., Harad, A. M. and Jawale, L. S. (2008) 'Recycling of waste PET into useful textile auxiliaries', *Waste Management*, 28(1), pp. 51–56. doi: 10.1016/j.wasman.2006.11.002.

Soekoco, A. S. *et al.* (2018) 'Recycled fiber from straw waste: Effect of take-up speed and spinneret diameter to linear density and tenacity', *MATEC Web of Conferences*, 154, pp. 2–5. doi: 10.1051/mateconf/201815401119.

Spektrima, T. (2009) *Pemanfaatan Limbah Polietilena Tereftalat ( Pet ) Sebagai Matrik Komposit Dengan Bahan Penguat Kaca Serat, Skripsi*. Universitas Sumatera Utara.

Tan, Y. *et al.* (2013) 'Grafting of copolymers onto graphene by miniemulsion polymerization for conductive polymer composites: Improved electrical conductivity and compatibility induced by interfacial distribution of graphene', *Polymer Chemistry*, 4(10), pp. 2939–2944. doi: 10.1039/c3py00164d.

Tzeng, S. S. and Chang, F. Y. (2001) 'Electrical resistivity of electroless nickel coated carbon fibers', *Thin Solid Films*, 388(1–2), pp. 143–149. doi: 10.1016/S0040-6090(01)00809-4.

Valentini, L. *et al.* (2016) 'Synergistic effect of graphene nanoplatelets and carbon black in multifunctional EPDM nanocomposites', *Composites Science and Technology*. Elsevier Ltd, 128, pp. 123–130. doi: 10.1016/j.compscitech.2016.03.024.

Wangsness, R. . (1986) *Electromagnetic Fields*. 2nd editio. chichester, West Sussex, UK: John Wiley & Sons, Ltd.

Ward, I. . and Sweeney, J. (2013) *Mechanical Properties of Solid Polymers*. chichester, West Sussex, UK: John Wiley & Sons, Ltd.

Wira Sakti, N. ( (2019) 'Bumi Dalam Kantong Plastik', *Media Keuangan*, XIV(144), pp. 1–30.

Xue, P. *et al.* (2007) 'Electrically conductive yarns based on PVA/carbon nanotubes', *Composite Structures*, 78(2), pp. 271–277. doi:

10.1016/j.compstruct.2005.10.016.

Xue, P. and Tao, X. M. (2005) 'Morphological and electromechanical studies of fibers coated with electrically conductive polymer', *Journal of Applied Polymer Science*, 98(4), pp. 1844–1854. doi: 10.1002/app.22318.

Yan, X. *et al.* (2016) 'Lowly loaded carbon nanotubes induced high electrical conductivity and giant magnetoresistance in ethylene/1-octene copolymers', *Polymer*, 103, pp. 315–327. doi: 10.1016/j.polymer.2016.09.056.

Zha, J. W. *et al.* (2016) 'Flexible electrospun polyvinylidene fluoride nanofibrous composites with high electrical conductivity and good mechanical properties by employing ultrasonication induced dispersion of multi-walled carbon nanotubes', *Composites Science and Technology*, 128, pp. 201–206. doi: 10.1016/j.compscitech.2016.04.002.

Zhang, Q. *et al.* (2017) 'Tunable electrical conductivity of carbon-black-filled ternary polymer blends by constructing a hierarchical structure', *Polymers*, 9(9). doi: 10.3390/polym9090404.

